

PRODIMAX

INSULATION & THERMAL SERVICES

COVER
PRO-TURBINE

Expert manufacturer of customized removable insulation covers, since 1996

Our quality insulating blankets are fabricated quickly and efficiently to suit a wide range of industrial equipment. Upon request, our representative will visit your facility to measure and install the covers, ensuring a perfect fit.



Recommended Temperatures

2000°F Maximum

Recommended Applications

- Interior / exterior
- Steam & gas turbines, high pressure valves

Fabrication

1st Layer - Exterior

- Tissu 2560

1st Layer - Isulation

- Insulite wool
- Glass Mat wool

1st Layer - Interior

- Mesh

Thread

- Stainless steel reinforced Kevlar®

2nd Layer - Exterior

- Tissu 7320 Grey

2nd Layer - Isulation

- Insulite wool

2nd Layer - Interior

- 2560

Technical specifications

2560

- Fiberglass cloth 24oz (1000°F) vermiculite coated (1000°F)

Glass Mat

- Fiberglass wool (1200°F)
- Density: 11 lbs

Mesh

- Stainless steel 304 Mesh (2200°F)

Thread

- Kevlar® / stainless steel (800°F)
- S-110 / 3 ply
- Resistance: 27 lbs

7320 Grey

- Fiberglass cloth 32oz (1000°F) impregnated with silicone (500°F)

Insulite

- Fiberglass wool (1000°F)
- Density: 4.5 lbs

Components

- Lacing anchors and stitching pins
- Stainless steel pin, T-304 18 gage

Product Made in Quebec

PRODIMAX

175, rue d'Amsterdam, local #2, St-Augustin-de-Desmaures (Quebec) G3A 2V5
Tel. : (418) 878-7132 Fax : (418) 878-7194 Email : info@prodimax.ca